



Art. GV9076/536AI



SPECIFICATION

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
Minimum Illumination	Color: 0.008 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
S/N Ratio	60db
WDR	120dB
PTZ	
Horizontal Rotation Speed	80°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	60°/sec
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	4.6mm-165mm; F1.6-F4.3
Focus Control	36X Optical Zoom
Night Vision	
Infrared LED	∅ 35x6PCS + 2PCS Laser LED
IR Range	150m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support (PROFILE S, PROFILE G, PROFILE T)
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream1	5MP(2592*1944)@20fps
Main Stream2	4MP(2560*1440)@25fps
Main Stream3	N/A
Sub Stream1	D1(720*480)@20fps
Sub Stream2	CIF(352*288)@20fps
AI Function	
Smart Analytic	Intrusion Detection, motion detection based on human detection, Sound Alarm
Tracking effective range	5~45M Speed: 3~12KM/h
Interface	
Audio	2-Way Audio
Audio Encode	G711A, C711U
Alarm	N/A
SD Card Slot	Optional
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	-40°C ~ +60°C
Operating Humidity	≤90% Non Condensing
Power	DC12/4A
Lightning Protection	Transient voltage 6000V
Dimension	∅ 20.4 X 32.4(cm)
Weight	2.28Kgs